

(19)

BOQ of satnam bhawan boundry wall ward no 30**PWD SOR 01.01.2015**

S No.	S.O.R. Ref	Description of item	Qty	Unit	Rate
1	2	3	4	5	6
1	1.1.1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits	175.58	cum	185.00
3	3.1.2	Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work.1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	11.23	cum	2659.00
4	2.1.1	Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.	114	sqm	139.00
6	2.1.5	Columns, Pillars, Piers and likes- rectangular or square in shape	86	sqm	297.00
9	3.2.1	Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of form work.1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mmnominal size).	41.56	cum	4163.00
10	3.14.1	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire in foundation and plinth all complete:Thermo-Mechanically treated bars	2078	kg	54.50
11	7.4.3 +7.6	Brick work with modular fly-ash lime bricks (FALG Bricks) confirming to IS:12894-2002 of class designation 40 in foundation and plinth in:	53.76	cum	3384
23	14.11	Wall painting with acrylic luxury emulsion (plastic) paint of required shade	572	sqm	52.50
38	9.14	Providing and fixing steel door made of angle iron of suitable sizes with M.S. grill of approved pattern made of M.S. flats or square or round bars coat of red oxide zinc chromate primer.	150	kg	79.50
39	11.3.4	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix:In Cement Mortar 1:4 (1 cement : 4 fine sand)	572	sqm	120.00

mdey